



FLX-Paint Customer Care & Warranty Statement Card

- Give this form to your customers so they know how to care for their FLX-Paint application and how to contact you for repairs and new business

Printing Instructions

- Print page 2, remove from printer, turn page over, re-insert into printer and print page 3. This will put the Customer Care instructions on one side and the Warranty Statement on the other
- Cut printed paper in half at dotted line to create two cards
- Attach your contact information in the box provided on Warranty Statement side



Congratulations on your FLX-Paint™ purchase



- FLX-Paint™ is produced using premium automotive paint. It will give you years of trouble free performance
- Because it's made with paint, FLX-Paint can be buffed & waxed. See instructions below for washing, waxing and detailing
- As with any car paint, do not expose FLX-Paint to chemicals not suitable for an automotive paint finish, including aftermarket silicone-based paint sealants. Do not expose to acid rain and grey water from sprinkler systems

Waxing / Polishing FLX-Paint™

- Wash using premium car wash detergent, dry completely and follow with a premium automotive polish to maintain FLX-Paint. NEVER apply silicone based sealants to FLX-Paint

Detailing FLX-Paint™

FLX-Paint should be detailed by a Professional detailer

- FLX-Paint™ has a 2 mil OEM grade automotive clear coat. Buff one time only - additional or excessive buffing reduces clear coat thickness & life of product. **DO NOT buff or polish Matte & Ultra Matte colors**
- Showroom Finish: Buff at 1000 rpm using 3000 grit buffing compound followed by premium polish

Removing debris or surface imperfections from FLX-Paint

1. Lightly hand wet sand with 1500 grit followed by light wet sand with 4000 grit
2. Machine buff at 1000 rpm with 3000 grit buffing compound and water. Use trigger head sprayer to spray water while buffing. **DO NOT buff or polish Matte & Ultra Matte colors**
3. Finish with premium polish



ACI recommends
Meguiar's Premium Polishes &
Car Care products

See other side for instructions on
removing FLX-Paint



Congratulations on your FLX-Paint™ purchase



- FLX-Paint™ is produced using premium automotive paint. It will give you years of trouble free performance
- Because it's made with paint, FLX-Paint can be buffed & waxed. See instructions below for washing, waxing and detailing
- As with any car paint, do not expose FLX-Paint to chemicals not suitable for an automotive paint finish, including aftermarket silicone-based paint sealants. Do not expose to acid rain and grey water from sprinkler systems

Waxing / Polishing FLX-Paint™

- Wash using premium car wash detergent, dry completely and follow with a premium automotive polish to maintain FLX-Paint. NEVER apply silicone based sealants to FLX-Paint

Detailing FLX-Paint™

FLX-Paint should be detailed by a Professional detailer

- FLX-Paint™ has a 2 mil OEM grade automotive clear coat. Buff one time only - additional or excessive buffing reduces clear coat thickness & life of product. **DO NOT buff or polish Matte & Ultra Matte colors**
- Showroom Finish: Buff at 1000 rpm using 3000 grit buffing compound followed by premium polish

Removing debris or surface imperfections from FLX-Paint

1. Lightly hand wet sand with 1500 grit followed by light wet sand with 4000 grit
2. Machine buff at 1000 rpm with 3000 grit buffing compound and water. Use trigger head sprayer to spray water while buffing. **DO NOT buff or polish Matte & Ultra Matte colors**
3. Finish with premium polish



ACI recommends
Meguiar's Premium Polishes &
Car Care products

See other side for instructions on
removing FLX-Paint



Made in USA

ACI warrants its FLX-Paint™ product line against paint delamination, accelerated paint fading, clear coat failure and adhesive failure for a period of 5 Years for horizontal application and 15 Years for vertical application for STANDARD colors. KANDY colors carry a 1 Year Warranty. Go to flxpaint.com for a list of Standard and Kandy colors.

Warranty Statement

Minimal fading is expected of all paint applications, including FLX-Paint™, over a period of years and the rate of fade is dependent on color, amount of exposure and geographic location. This warranty covers rapid, unnatural fading.

This warranty does not cover failure due to improper installation, neglect, exposure to chemicals not suitable for an automotive paint finish, aftermarket silicone-based paint sealants, excessive or over-buffing, exposure to acid rain and grey water from sprinkler systems. Consult the FLX-Paint care guide on the other side for buffing, polishing & maintenance instructions.

Because applications and conditions vary under which FLX-Paint™ is used, ACI cannot warrant results for use of FLX-Paint beyond the cost of replacement of nonusable material. No representation other than this is authorized by ACI.

Removing FLX-Paint™

FLX-Paint™ is removable; removes cleanly up to 5 years after application. Car's original paint is fully protected. Contact your Professional FLX-Paint Installer for more information

Applied Coatings International LLC reserves the right to make changes at any time, without notice, in price, colors, materials, specifications, product selection and warranty terms. 2010 Applied Coatings International LLC



Applied Coatings International LLC
25104 S. 4170 Road
Claremore, OK. 74019 USA
918-283-2938
www.flxpaint.com

FLX-Paint is available from



Made in USA

ACI warrants its FLX-Paint™ product line against paint delamination, accelerated paint fading, clear coat failure and adhesive failure for a period of 5 Years for horizontal application and 15 Years for vertical application for STANDARD colors. KANDY colors carry a 1 Year Warranty. Go to flxpaint.com for a list of Standard and Kandy colors.

Warranty Statement

Minimal fading is expected of all paint applications, including FLX-Paint™, over a period of years and the rate of fade is dependent on color, amount of exposure and geographic location. This warranty covers rapid, unnatural fading.

This warranty does not cover failure due to improper installation, neglect, exposure to chemicals not suitable for an automotive paint finish, aftermarket silicone-based paint sealants, excessive or over-buffing, exposure to acid rain and grey water from sprinkler systems. Consult the FLX-Paint care guide on the other side for buffing, polishing & maintenance instructions.

Because applications and conditions vary under which FLX-Paint™ is used, ACI cannot warrant results for use of FLX-Paint beyond the cost of replacement of nonusable material. No representation other than this is authorized by ACI.

Removing FLX-Paint™

FLX-Paint™ is removable; removes cleanly up to 5 years after application. Car's original paint is fully protected. Contact your Professional FLX-Paint Installer for more information

Applied Coatings International LLC reserves the right to make changes at any time, without notice, in price, colors, materials, specifications, product selection and warranty terms. 2010 Applied Coatings International LLC



Applied Coatings International LLC
25104 S. 4170 Road
Claremore, OK. 74019 USA
918-283-2938
www.flxpaint.com

FLX-Paint is available from